



## Operating Instructions

### Electric Hot Water Pressure Cleaner

Congratulations on the purchase of your new electric hot water pressure cleaner. Before attempting to operate your machine, please read all of the instructions to ensure safe and trouble free service from your cleaning machine.

#### Component Checklist

The following standard accessories should have accompanied your machine: -

- (1) Hose assembly;
- (2) Gun and lance assembly;
- (3) Manufacturers motor and pump assembly specifications;
- (4) Warranty card;
- (5) Detergent line with filter.

Contact your point of purchase immediately if any of the above components are missing.

#### Pre-Operation Instructions

- (1) Ensure that the machine is switched off before proceeding with the following instructions.
- (2) Connect the high-pressure hose to the pump outlet.
- (3) Connect the water supply to the inlet water fitting on the pump. Ensure that the water supply is sufficient for the operation of the pump, if you are uncertain of the suitability of the water supply then refer to the recommended flow rate, which is displayed on the data plate on the pump body.
- (4) Ensure that the water inlet supply filter is not blocked due to the presence of foreign particles in the water supply. Clean the water inlet supply filter regularly to ensure smooth operation.
- (5) Check that the oil level on the pump indicates the correct level.

#### (6) OPERATION

- (i) **Read the chapter on safety precautions before proceeding to use this machine;**
- (ii) Turn water supply ON
- (iii) **\*\*\*Ensure twin lance is set to low pressure for start up\*\*\***
- (iv) Switch machine to ON position
- (v) Switch the Burner to the ON position and set the thermostat to the required temperature
- (vi) Point the lance towards the object to be cleaned and depress the trigger on the gun;
- (vii) If using a twin lance, ensure that the tap handle on the lance is on the 'off' position for optimum pressure. On this high pressure operation the water should only come out of the stainless steel high pressure jet;
- (viii) To reduce pressure, or, operate on low pressure for detergent, open the low-pressure handle on the twin lance.

#### (7) Chemical Injection Operation

- (i) Insert the filter end of the clear detergent hose into the container holding the cleaning detergent to be used and affix the opposite end to the chemical injector;
- (ii) Turn the knob on the chemical injector anticlockwise to adjust the flow of the detergent;
- (iii) To reduce pressure, or, operate on low pressure for detergent, open the low-pressure handle on the twin lance.



## (8) To end operation

- (i) Switch the machine Burner OFFF at the on/off switch;
- (ii) Continue to run cold water through the Gun/Lance to cool the heating coil  
**###Continue to cool for approximately 60 seconds###**
- (iii) Switch the power point off and disconnect plug from the power point;
- (iv) Turn the inlet water off at the tap;
- (v) Pull the trigger on the gun to release any backpressure;
- (vi) Disconnect both the water inlet supply hose and the water outlet high-pressure hose.

### Important Safety Precautions

- (1) Never direct the spray jet at any person or animal;
- (2) Never place any part of your body over the nozzles;
- (3) Never direct the spray jet towards either the machine itself or any electrical item;
- (4) After use, pull the trigger on the gun to release any backpressure;
- (5) When not in use, ensure that the machine is switched off and is disconnected from both power supply and inlet water supply;
- (6) Do not attempt any mechanical repair yourself. Should your machine require either service or repair then please contact your local Jetwave agent;
- (7) Never supply any liquid other than water to the water inlet;
- (8) Never pull on the high pressure hose if it has formed kinks or nooses;
- (9) Never drag the hose over sharp objects;
- (10) Do not attempt to disconnect either the hose or any couplings whilst there is pressure in the hose. Refer to point (4) above.
- (11) Do not operate the machine whilst on a ladder;
- (12) Never allow children to either operate or play with the machine;
- (13) The use of safety glasses is recommended when using the machine to prevent any loose particles disturbed by the high-pressure spray coming into contact with your eyes.

### Use

#### CHECKS BEFORE USE

- Check that there is Diesel in the fuel tank, if not, fill up;
- Check that the thermostat is in "O" °C position;
- Start the machine acting in the opposite (ON/OFF) burner switch and wait for 30 seconds to obtain the filling of gas oil pump, act on the thermostat knob and put the temperature selector at 90° C for almost 30 seconds, select the water working temperature acting on the same knob.

### Tips & Hints

- (1) Regularly check the oil level in the pump. The oil level should be maintained at the level indicated on the pump.
- (2) Top up the oil in the pump when required using SAE 20W 50 oil. Never mix different grades of oil.
- (3) Use a good quality 13mm (inside diameter) water supply hose and connect to the water inlet on the water tank, ensure that this connection is tight to avoid leaks.
- (4) Ensure that the tap on the water supply is fully opened before operating the machine.



- (5) Where possible, avoid the use of long extension leads as these will cause the machine to overheat and will void warranty.
- (6) After detergent use, flush the machine for a few minutes with clean water.

**Burner Maintenance**

- (7) The burner installed on our high pressure cleaner, runs only with Diesel. Periodically check and clean the filters and the fuel nozzle, we recommend the replacement of the same every 400 working hours.

**Coil**

- (8) If the coil is covered in soot, you should check the burner at the Customer Service Centre.

**Trouble Shooting**

The following table is provided as a general guide only. Please refer to your local Jetwave agent for service, repairs or specific advice.

Fault	Probable Cause	Possible Remedy
Pump runs normally but pressure does not achieve rated value.	Pump is sucking air.  Valves are worn or dirty.  Unloader valve packaging worn.  Nozzle incorrect or worn.  Worn piston packing.  Dirty filter.	Check that all hoses and fittings are airtight.  Check, clean or replace.  Check and replace.  Check and replace.  Check and replace.  Check and clean.
Fluctuating pressure.	Valves dirty, worn or stuck.  Pump sucking air.  Worn piston packing.  Dirty filter.	Check, clean or replace.  Check that all hoses and fittings are airtight.  Check and relace.  Check and clean.
Presence of water in oil.	High humidity in air.  Piston packing or oil seal worn.  Water entering through breather.	Check and change oil twice as often.  Check and replace.  Excessive water on machine.
Water dripping from pump.	Piston packing worn.  Piston guide o’rings worn.	Check and replace.  Check and replace.
Dripping oil.	Worn oil seals.  Oil coming out of breather.	Check and replace.  Pump oil level overfull.



Motor does not start when switched on.	<p>Plug not well-connected or unreliable power supply.</p> <p>Earth leakage overload.</p>	<p>Check plug, cable and switch.</p> <p>Check earth leakage.</p>
When switched on the motor hums but does not run.	Mains voltage is insufficient.	Check adequacy of mains power supply.
Motor stops suddenly during operation.	Thermal overload tripped due to overheating.	Check mains voltage for fluctuations.
The water does not reach working temperature.	<p>Damaged thermostat.</p> <p>Thermostat adjusted too low.</p> <p>Scale in the hydraulic system.</p> <p>Sooted boiler.</p>	<p>Replace.</p> <p>Place the thermostat at the required temperature.</p> <p>Contact the Maintenance Service.</p> <p>Contact the Maintenance Service.</p>
The boiler is smoking.	<p>Water in the gas oil tank.</p> <p>Incorrect gas oil pressure.</p> <p>Electrodes improperly positioned.</p> <p>Fuel nozzle dirty.</p> <p>Fuel nozzle worn out.</p> <p>Heating coil blocked by soot.</p> <p>Gas oil pump dirty.</p> <p>Gas oil solenoid valve not working.</p>	<p>Completely drain the gas oil tank then, fill up with clean gas oil.</p> <p>Turn the adjusting screw until obtaining approx. 10 bar; contact the Maintenance Service.</p> <p>Adjust the difference between the electrodes; contact the Maintenance Service.</p> <p>Clean the fuel nozzle.</p> <p>Replace the fuel nozzle.</p> <p>Clean the heating coil.</p> <p>Disassemble the pump and clean the filter; contact Maintenance Service.</p> <p>Replace the solenoid valve.</p>



<p>The burner cut out during operation.</p>	<p>Gas oil tank empty.</p> <p>Water in the gas oil tank.</p> <p>Fluxostath damaged.</p> <p>Starting transformer damaged.</p> <p>Rotation of the starting electrodes.</p> <p>Gas oil nozzle dirty.</p> <p>Gas oil nozzle damaged.</p> <p>Gas oil pump damaged.</p> <p>Gas oil solenoid valve damaged.</p>	<p>Fill up the gas oil tank.</p> <p>Completely drain the gas oil tank and fill up with clean gas oil.</p> <p>Replace the fluxostath.</p> <p>Replace the transformer.</p> <p>Set the electrodes back to their proper position; contact the Maintenance Service.</p> <p>Clean the nozzle.</p> <p>Replace the nozzle.</p> <p>Replace the gas oil pump.</p> <p>Replace the gas oil solenoid valve.</p>
---	--	--

## **STANDARD OPERATING PROCEDURES**

### **HIGH PRESSURE CLEANERS**

#### **SPECIAL INSTRUCTION:**

1. High pressure cleaning should be carried out in an area isolated from other workers, or steps taken to prevent exposure of persons to the cleaning process.
2. Persons should not operate high pressure cleaners unless they have been instructed in the hazards and the means of safe use of the equipment.
3. All persons using high pressure cleaners are to use personal protective equipment appropriate for the task and the equipment used.

Task sequence	Identified hazards in task	Key processes to be followed	Precautions / PPE required
1. Preparation	<p>Electric Shock</p> <p>Skin irritation</p> <p>Burns, risk of fire</p>	<p>Care must be taken to ensure that electric leads are kept out of water, and preferably above ground.</p> <p>Follow manufacture's instructions when adding cleaning agents to cleaners.</p> <p>Exercise caution when igniting gas or oil burners on steam cleaners.</p>	<p>Safety switch or RCD must be used.</p> <p>Hand protection must be worn.</p> <p>No smoking in vicinity.</p>

2. Operation	Foreign matter in eyes  Skin irritation  Burns Slips and falls Noise	Water splash will contain cleaning agent and foreign matter from article being cleaned, which may splash back towards operator. Overspray and splash back will result in operator's clothing becoming wet with contaminated water from cleaner. Protect hands from hot water and heat from lance. Keep work areas clean – remove grease and other matter from floors. Larger units and steam cleaners may generate unsafe noise levels.	Wear safety goggles and/or face shield.  Wet weather clothing and waterproof footwear required. Wear PVC gloves.  Wear hearing protection.
3. Risks to other persons	Splashing	The distance that water will be ejected over depends on the shape and velocity of the water jet. Exclusion of persons other than those actually involved in the cleaning task should be made to prevent injury from water and water-borne particles and cleaning agents.	Prevent unauthorised entry into are where cleaning is being carried out.

**PRECAUTIONS;**

1. The following precautions should be observed when carrying out this procedure.
2. Where applicable, suitable safety and warning signs should be displayed in areas where this procedure is carried out.

Preparation	Operation	Risk to other persons
		